

ARF LUBRICANT

SG 20W60

DESCRIPTION

ARF LUBRICANT SG 20W60 is premium motor oil intended for use in older gasoline-powered passenger cars with turbochargers and naturally aspirated engines, as well as light-duty diesel vehicles. To offer superior engine protection, a blend of performance additives and carefully chosen premium quality base oils is used. This product was created to surpass API (American Petroleum Institute) SG performance standards.

CHARACTERISTICS

SPECIFICATION	TEST METHOD	Value
Density @ 15°C, kg/l	D 1298	0.8-1
Viscosity @ 100 °C, cSt.	D 445	23.5-26.1
Viscosity Index	D 2270	Min 125
Flash Point, °C	D 92	Min 220
Pour Point, °C	D 97	Max -24
TBN, mg KOH/g	D 2896	Min 4
CCS, cP	D 5293	Max 9500
% Volatility by Noack, wt	D 5800	Max 10

ADVANTAGES

- Sludge and deposit accumulation is reduced via improved thermo-oxidative stability.
- Rust in crucial engine parts is postponed by effective rust inhibitors.
- Engine wear is minimized by improved antiwear technology, which lowers maintenance expenses.
- Reliable lubrication is ensured even at higher loads and operating temperatures by good stay-in-grade performance.