

ARF LUBRICANT

SG 20W50

DESCRIPTION

ARF LUBRICANT SG 20W50 is premium motor oil intended for use in older gasoline-powered passenger cars with turbochargers and naturally aspirated engines, as well as light-duty diesel vehicles. To offer superior engine protection, a blend of performance additives and carefully chosen premium quality base oils is used. This product was created to surpass API (American Petroleum Institute) SG performance standards.

CHARACTERISTICS

| SPECIFICATION | TEST METHOD | Value |
|---------------------------|-------------|-----------|
| Density @ 15°C, kg/l | D 1298 | 0.8-1 |
| Viscosity @ 100 °C, cSt. | D 445 | 18.5-21.5 |
| Viscosity Index | D 2270 | Min 115 |
| Flash Point, °C | D 92 | Min 220 |
| Pour Point, °C | D 97 | Max -24 |
| TBN, mg KOH/g | D 2896 | Min 4 |
| CCS, cP | D 5293 | Max 9500 |
| % Volatility by Noack, wt | D 5800 | Max 10 |

ADVANTAGES

- Sludge and deposit accumulation is reduced via improved thermo-oxidative stability.
- Rust in crucial engine parts is postponed by effective rust inhibitors.
- Engine wear is minimized by improved antiwear technology, which lowers maintenance expenses.
- Reliable lubrication is ensured even at higher loads and operating temperatures by good stay-in-grade performance.