

# ARF LUBRICANT

## SL 10W40

### DESCRIPTION

**ARF LUBRICANT SL 10W40** is a high-quality, premium motor oil designed for modern, multi-valve, high-output, turbocharged, and supercharged gasoline passenger cars and light-duty diesel vehicles. Even though every grade is designed to surpass API (American Petroleum Institute) SL performance standards.

### CHARACTERISTICS

| SPECIFICATION             | TEST METHOD | Value     |
|---------------------------|-------------|-----------|
| Density @ 15°C, kg/l      | D 1298      | 0.8-1     |
| Viscosity @ 100 °C, cSt.  | D 445       | 14.2-16.2 |
| Viscosity Index           | D 2270      | Min 140   |
| Flash Point, °C           | D 92        | Min 200   |
| Pour Point, °C            | D 97        | Max -30   |
| TBN, mg KOH/g             | D 2896      | Min 6     |
| CCS, cP                   | D 5293      | Max 7000  |
| % Volatility by Noack, wt | D 5800      | Max 15    |

### ADVANTAGES

- Excellent dispersants offer superior control over oil thickening caused by soot.
- Improved thermo-oxidative stability reduces the accumulation of deposits and sludge, allowing for a longer oil life.
- Engine cleanliness is provided by active cleaning agents.
- Engine wear is minimized with good anti-wear technology, which lowers maintenance costs.
- Certain engine parts are protected from rust and corrosion by special rust inhibitors.