

ARF LUBRICANT

SN 10W40

DESCRIPTION

ARF LUBRICANT SN 10W40 is a cutting-edge motor oil designed specifically for today's high-output, turbocharged gasoline engines seen in vans, light-duty trucks, sport utility vehicles, and passenger automobiles. This oil helps safeguard engines even when they are running on ethanol-containing fuels up to E85 and offers superior protection against wear, deposits, and sludge build-up. These grades are designed to preserve fuel efficiency and safeguard turbocharger and vehicle emission systems.

CHARACTERISTICS

SPECIFICATION	TEST METHOD	Value
Density @ 15°C, kg/l	D 1298	0.8-1
Viscosity @ 100 °C, cSt.	D 445	14.2-16.2
Viscosity Index	D 2270	Min 140
Flash Point, °C	D 92	Min 200
Pour Point, °C	D 97	Max -30
TBN, mg KOH/g	D 2896	Min 6
CCS, cP	D 5293	Max 7000
% Volatility by Noack, wt	D 5800	Max 15

ADVANTAGES

- Advanced additive technology combined with premium base fluids makes these oils very strong in improving sludge protection, piston cleanliness, turbocharger protection, interoperability good sealing, anti-wear protection, and compatibility with fuels containing ethanol up to E85.
- Outstanding shear stability and excellent resistance to oil oxidation Provide excellent lubrication at low temperatures and engine protection at high temperatures.
- Special friction modifiers used in this oil help improve and maintain fuel economy.
- Outstanding evaporation properties help reduce oil consumption and oil contamination.