

ARF LUBRICANT

SL 20W50

DESCRIPTION

ARF LUBRICANT SL 20W50 is a high-quality, premium motor oil designed for modern, multi-valve, high-output, turbocharged, and supercharged gasoline passenger cars and light-duty diesel vehicles. Even though every grade is designed to surpass API (American Petroleum Institute) SL performance standards.

CHARACTERISTICS

SPECIFICATION	TEST METHOD	Value
Density @ 15°C, kg/l	D 1298	0.8-1
Viscosity @ 100 °C, cSt.	D 445	18.5-21.5
Viscosity Index	D 2270	Min 115
Flash Point, °C	D 92	Min 220
Pour Point, °C	D 97	Max -24
TBN, mg KOH/g	D 2896	Min 6
CCS, cP	D 5293	Max 9500
% Volatility by Noack, wt	D 5800	Max 10

ADVANTAGES

- Excellent dispersants offer superior control over oil thickening caused by soot.
- Improved thermo-oxidative stability reduces the accumulation of deposits and sludge, allowing for a longer oil life.
- Engine cleanliness is provided by active cleaning agents.
- Engine wear is minimized with good anti-wear technology, which lowers maintenance costs.
- Certain engine parts are protected from rust and corrosion by special rust inhibitors.